

# Anzi External Motors



#### Motors

**1**61

А

1400m³/hr - 6" Outlet 2000m³/hr - 8" Outlet

## EEI Rating

## **Duct Size**

1400m<sup>3</sup>/hr - 150mm Minimum Round or Rectangular Equivalent

2000m³/hr - 200mm Minimum Round or Rectangular Equivalent

# **Remote Control**

Yes

## Box Dimensions (CM) & Weight

60cm x 60cm Body 120cmx30cm Body 90cmx50cm Body 120cmx50cm Body Flat Roof Motor Pitched Roof Motor Wall Motor

74x74x40	9,7kg
131x39x24	12kg
106x63x36	13,7kg
144x58x55	16,7Kg
64.5x51x76.5	19kg
58.5x48.5x38	13.9kg
58.5x48.5x38	13.9kg

# Lighting

60cm x 60cm 120xm x 30cm 90cm x 50cm 120cm x 50cm 4x LED Spots 1,2w 4000° Kelvin 4x LED Spots 1,2w 4000° Kelvin 6x LED Spots 1,2w 4000° Kelvin 8x LED Spots 1,2w 4000° Kelvin

# Warranty

7 Years (Parts & Labour) Subject to Registration Our external motors are designed with a round 6" or 8" ducting outlet.

- 1400m<sup>3</sup>/hr motors have a 6"/150mm outlet. Adapters <u>will not</u> fit directly on to the motor exhaust. A small piece of round ducting will be required to fit on to the outlet first. These motors can be ducted up to 6m.
- 2000m<sup>3</sup>/hr motors have a 8"/200mm outlet. Adapters <u>will</u> fit directly on to the motor exhaust. Round plastic ducting pipe will not fit on to the outlet. These motors can be ducted up to 8m.

\*Please see all available options on our website



## Flat Roof Motor



## Pitched Roof Motor



## Wall Mounted Motor



